Topics and Techniques for Forensic DNA Analysis **Continuing Education Seminar**

Capillary Electrophoresis **Fundamentals**

and Troubleshooting

NYC OCME **Dept of Forensic Biology**

New York City, NY March 25, 2009



Dr. John M. Butler National Institute of Standards and Technology

john.butler@nist.gov

Presentation Outline

- · History and background on CE
- Separation
- · Injection and sample preparation
- Detection
- Troubleshooting

Mv Goal:

To help you understand the basic chemistry behind DNA separations and to help make CE instruments less of a "black box"

Pioneers of Capillary Electrophoresis



Stellan Hjertén

1967

First high voltage CE

system (with rotating 3 mm i.d. capillaries)

James Jorgenson University of North Carolina



Barry Karger

1981

First "modern" CE experiments (with 75 µm i.d. capillaries)

1988/90

First DNA separations in a capillary (gel-filled/ sieving polymer)

Stellan Hjertén

Uppsala University (Sweden)



With first fully automated capillary free zone electrophoresis apparatus in 1967

Arne Tiselius who had developed moving boundary zone electrophoresis in 1937 (Noble Prize in 1948)

In 2003 at age 75

A Brief History of Capillary Electrophoresis

- 1937 Tiselius develops moving boundary electrophoresis
- 1967 Hjertén uses rotating 3 mm i.d. tubes for CE
- 1981 Jorgenson and Lukacs demonstrate first high performance CE separations with 75 μm i.d. capillary
- 1988 Karger's group shows DNA separations of single stranded oligonucleotides with gel-filled capillaries
- 1990 Karger's group shows DNA separations with sieving polymers on DNA restriction fragments
- 1991 Grossman expands work with sieving polymers
- 1992 Bruce McCord starts working on PCR product separations with STR allelic ladders

My Experience with CE, STRs, etc.

- May 1993 began working in Bruce McCord's lab at Quantico
- Sept 1993 developed mtDNA amplicon quantitation method (used in FBI casework from 1996 to present)
- Nov 1993 first demonstration of STR typing by CE (using dual internal standards and TH01 ladder)
- July 1995 defended Ph.D. dissertation entitled "Sizing and Quantitation of Polymerase Chain Reaction Products by Capillary Electrophoresis for Use in DNA Typing"
- July 1995 ABI 310 Genetic Analyzer was released

My Experience with CE, STRs, etc. (cont.)


- 1996-1997 Developed STRBase while a postdoc at NIST
- Nov 1998 GeneTrace Systems purchased a 310; typed several hundred samples with Profiler Plus and Cofiler kits and compared results to mass spec STR analysis
- 1999-present Run thousands of samples with all STR kits available (except PP 1.2) and developed a number of new STR multiplex systems
- Jan 2001 Published "Forensic DNA Typing: Biology and Technology behind STR Markers" (2nd Edition in Feb 2005)
- April 2001-present Use of ABI 3100 16-capillary array system


In the early 1990s the real question was how to transition from a gel to a capillary

- Cross-linked acrylamide gel filled capillaries were tried first
 - Reusable?
 - Bubble formation
 - Themal degradation
- · Alternative was to not use a gel at all
 - Refillable sieving polymers
 - However, resolution was poor early on

Early Work with CE and STRs


- Barry Karger's group (1988-1990)
 - Utilized gel-filled capillaries to separate ssDNA
 - Introduced sieving polymers in the form of linear polyacrylamide to separate restriction digests
- Beckman P/ACE 2050 is introduced in 1992 as the first commercially available CE coupled to a laser to enable fluorescence detection
- John Butler and Bruce McCord (1993-1995)
 - First STR typing with single color CE using intercalating dyes and dual bracketing internal size standards
- Rich Mathies' group (1995)
 - First STR typing with multi-color CE (and multi-capillary) using dye-labeled primers
- ABI 310 is introduced in July 1995 as the first commercially available multi-color CE








Why Use CE for DNA Analysis? 1. Injection, separation, and detection are automated. 2. Rapid separations are possible 3. Excellent sensitivity and resolution 4. The time at which any band elutes is precisely determined 5. Peak information is automatically stored for easy retrieval Symbol first used in Oct 1994 at the Promega meeting when I had a poster introducing the


use of CE for STR typing




















Process Involved in 310/3100 Analysis

- Separation
 - Capillary 50um fused silica, 43 cm length (36 cm to detector)
 - POP-4 polymer Polydimethyl acrylamide
 - Buffer TAPS pH 8.0
 - Denaturants urea, pyrolidinone
- Injection
 - electrokinetic injection process (formamide, water)
 - importance of sample stacking
- Detection
 - fluorescent dyes with excitation and emission traits
 - CCD with defined virtual filters produced by assigning certain pixels


Separation

Ohm's Law

- $\bullet \quad V = IR \ (\text{where V is voltage, I is current, and R is resistance})$
- Current, or the flow of ions, is what matters most in electrophoresis
- CE currents are much lower than gels because of a higher resistance in the narrow capillary
- CE can run a higher voltage because the capillary offers a higher surface area-to-volume ratio and can thus dissipate heat better from the ion flow (current)


DNA and Electrophoresis "From a practical point of view it is disappointing that electrophoresis cannot be used to fractionate or analyze DNA's on the basis of size" Olivera, Biopolymers 1964, 2, 245 $\mu_{ep} = q/6\pi \eta r \qquad \begin{array}{c} \text{small ions with high charge move fastest} \\ \hline A & T & G & C \\ \hline PO & PO & PO \end{array}$ As size increases so does charge!

NYC OCME Forensic Biology Continuing Education Seminar





Separation Issues

- Electrophoresis buffer -
 - Urea for denaturing and viscosity
 - Buffer for consistent pH
 - Pyrolidinone for denaturing DNA
 - EDTA for stability and chelating metals
- Polymer solution -- POP-4 (but others work also)
- Capillary wall coating -- dynamic coating with polymer
 - Wall charges are masked by methyl acrylamide
- Run temperature -- 60 °C helps reduce secondary structure on DNA and improves precision. (Temperature control affects DNA sizing)



Entangled Polymer Solutions Polymers are not cross-linked (above entanglement threshold) "Ge!" is not attached to the capillary wall Pumpable -- can be replaced after each run Polymer length and concentration determine the separation characteristics Examples: - 1% HEC (hydroxyethyl cellulose) - 4% polyvinyl pyrolidinone - POP-4 and POP-6 Polydimethyl acrylamide








What is in POP-4 and Genetic Analyzer Buffer? | Direct Opening University Press | Nucleic Acids Received, 1997, 164, 25, No. 19-3925-3929 | | Improved single-strand DNA sizing accuracy in capillary electrophoresis | Barnett B. Rosenblum*, Frank Oaks, Steve Menchen and Ben Johnson | | PE Applied Biosystems, 850 Lincoln Cartris Drive, Foster City, CA 94404, USA | | Incomed May 28, 1997 Revised and Ancepted Applied in 1997 | | See also Wenz et al. (1998) Genome Research 8: 69-80 | | POP-4 (4% poly-dimethylacrylamide, 8 M urea, 5% 2-pyrrolidinone) | | US Patent 5,552,028 covers POP-4 synthesis | | Running buffer contains 100 mM | | TAPS and 1 mM EDTA (adjusted to pH 8.0 with NaOH) TAPS = N-Tiris-(hydroxymethyl/methyl-3-aminopropane-sulfonic acid


Why TAPS instead of Tris-borate (TBE) buffer?

- TBE is temperature/pH sensitive
 - as temperature increases, the pH decreases (0.02 pH units with every 1 °C); this is the principle by which TaqGold activation works
- At lower pH, fluorescence emission of dyes decreases
 - see Singer and Johnson (1997) Proceedings of the Eighth International Symposium on Human Identification, pp. 70-77
- Thus when running at 60 °C on the ABI 310, if Tris-borate was used, fluorescent intensity of PCR products would be lower














How to Improve Resolution? 1. Lower Field Strength 2. Increase Capillary Length 3. Increase Polymer Concentration 4. Increase Polymer Length























Steps Performed in Standard Module


See J.M. Butler (2005) Forensic DNA Typing, 2nd Edition; Chapter 14

- Capillary fill polymer solution is forced into the capillary by applying a force to
- Pre-electrophoresis the separation voltage is raised to 10,000 volts and run
- Water wash of capillary capillary is dipped several times in deionized water to remove buffer salts that would interfere with the injection
- Sample injection the autosampler moves to position A1 (or the next sample in the sample set) and is moved up onto the capillary to perform the injection; a voltage is applied to the sample and a few nanoliters of sample are pulled onto the end of the capillary; the default injection is 15 kV (kilovolts) for 5 seconds
- Water wash of capillary capillary is dipped several times in waste water to remove any contaminating solution adhering to the outside of the capillary Water dip capillary is dipped in clean water (position 2) several times

- Water tip capinary is clipped in local water (published) expectal times Electrophoresis autosampler moves to inlet buffer vial (position 1) and separation voltage is applied across the capillary, the injected DNA molecules begin separating through the POP-4 polymer solution Detection data collection begins; raw data is collected with no spectral deconvolution of the different dye colors; the matrix is applied during Genescan analysis

Typical Sample Preparation for ssDNA

- 1. Perform PCR with dye-labeled primers
- 2. Dilute 1 μ L PCR product with 24 μ L **deionized formamide**; add 1 μ L ROX-labeled internal sizing
- 3. Denature 2 minutes at 95 °C with thermocycler
- 4. Cool to 4 °C in thermocycler or ice bath
- 5. Sample will remain denatured for at least 3 days



Comments on Sample Preparation

- Use high quality formamide (<100 μS/cm)!
 - ABI sells Hi-Di formamide
 - regular formamide can be made more pure with ion exchange
- · Deionized water vs. formamide
 - Biega and Duceman (1999) J. Forensic Sci. 44: 1029-1031
 - Crivellente, Journal of Capillary Electrophoresis 2002, 7 (3-4), 73-80.
 - water works fine but samples are not stable as long as with formamide; water also evaporates over time...
- · Denaturation with heating and snap cooling
 - use a thermal cycler for heating and cold aluminum block for snap cooling
 - heat/cool denaturation step is necessary only if water is substituted for formamide...

January 6, 2005 Letter from Applied Biosystems to ABI 310 Customers

- "Testing has shown that Hi-Di Formamide denatures DNA without the need to heat samples..."
- In other words, no heat denaturation and snap cooling needed!

Applied Biosystems Okays Use of Deionized Water for DNA Sequencing

Technical Bulletin #1

Applied Biosystems 3730/3730xl DNA Analyzer

Subject: Influence of Sequencing Injection Solution on 3730/3730xl DNA Analyzer Performance

In this Bulletin:

- Three Loading Solutions Tested on Page 1 Loading Solution Test Data on Page 2
- Recommendations on Page 6
 Guidelines for Use on Page 6

Three Loading Solutions Tested

Loading Solution Background

Dosums Soution Background Applied Biosystems presently recommends the use of Hi-Di^{TM} Formamide as the sample-loading solution for all Applied Biosystems DNA sequences to ensure sample preservation and resistance to exporation. However, many users of the 3730 choose either decinized water or dilute EDTA solutions. These choices are driven largely by cost and safety-hazardous material

Detection

Detection Issues

- · Fluorescent dyes
 - spectral emission overlap
 - relative levels on primers used to label PCR products
 - dye "blobs" (free dye)
- · Virtual filters
 - hardware (CCD camera)
 - software (color matrix)

Filters determine which wavelengths of light are collected onto the CCD camera


Laser Used in ABI 310


- · Argon Ion Laser
- 488 nm and 514.5 nm for excitation of dyes
- 10 mW power
- Lifetime ~5,000 hours (1 year of full-time use)
- Cost to replace ~\$5,500
- Leads to highest degree of variability between instruments and is most replaced part
- Color separation matrix is specific to laser used on the instrument


Methods for Fluorescently Labeling DNA Intercalating Dyes (post-PCR) Dye-labeled nucleotide insertion during PCR Dye-labeled primer insertion during PCR Fibrescent dNTPs are incorporated into both strands of PCR product Intercalating dye DNA labeled with intercalating dye One strand of PCR product is labeled with fluorescent dye labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand of PCR product is labeled with fluorescent dye Intercalating dye One strand dye One st

Fluorescent Labeling of PCR Products

- Dyes are attached to one primer in a pair used to amplify a STR marker
- Dyes are coupled to oligonucleotides (primers) through NHS-esters and amine linkages on the 5'end of the primer: Dye-(CH₂)₆-primer
- Dye-labeled oligonucleotides are incorporated during multiplex PCR amplification giving a specific color "tag" to each PCR product
- PCR products are distinguished using CCD imaging on the 310








Please Note!

- There are no filters in a 310
- Its just the choice of pixels in the CCD detector
- · All the light from the grating is collected
- · You just turn some pixels on and some off





Why Make a Matrix?


The matrix is the solution to a problem: What's the contribution at any given wavelength (filter set) from each dye?

There are 4 dyes


- Remember algebra from high school?
- To solve a problem with 4 unknowns, you need 4 equations








NYC OCME Forensic Biology Continuing Education Seminar





Comments on Matrices/Spectral Calibration (Multi-Component Analysis)


- Make sure that the right filter set and matrix are applied when collecting data
- You can always apply another matrix to a sample collected on the ABI 310 but it must be run with the right filter set (matrix must be run first with ABI 3100)
- It is important to update matrices on a regular basis (depending on use) due to differences in laser power over time
- A good indication of when to run a new matrix is the observation of pull-up between dye colors when peaks are smaller than ~4,000 RFUs



Dye Blobs ("Artifacts") • Free dye (not coupled to primer) can be injected into the CE capillary and interfere with detection of true STR alleles • Dye blobs are wider and usually of less intensity than true STR alleles (amount depends on the purity of the primers used) • Dye blobs usually appear at an apparent size that is unique for each dye (e.g., FAM ~120 bp, PET ~100 bp) Poor primer purity HEX dye blob DYS437







Conclusions

DNA typing by capillary electrophoresis involves:

- 1) The use of entangled polymer buffers
- 2) Injection by sample stacking
- 3) Multichannel laser induced fluorescence
- 4) Internal and external calibration

Practical Aspects of ABI 310/3100 Use


ABI Genetic Analyzer Usage at NIST

- ABI 310 x 2 (originally with Mac, then NT)
 - 1st was purchased in 1996
 - 2nd was purchased in June 2002
- ABI 3100 (Data collection v1.0.1) Jan 2007 – upgraded to 3130xl with data collection v3.0
 - Purchased in June 2002
 - Original data collection software retained
- ABI 3130xl upgrade (Data collection v3.0)
 - Purchased in April 2001 as ABI 3100
 - Upgraded to ABI 3130xl in September 2005
 - Located in a different room


Our Use of the ABI 3100

- Data collection software, version 1.0.1
- POP-6 with 36 cm capillary array
- STR kits and in-house assays for autosomal STRs, Y-STRs, and miniSTRs
- SNaPshot assays for mtDNA SNPs, Y-SNPs, and autosomal SNPs
- DNA sequencing for mtDNA and STR repeat sequencing

We can routinely get more than 400 runs per capillary array by not changing the polymer between applications



NYC OCME Forensic Biology Continuing Education Seminar



Consumables for ABI 310/3100

What we use at NIST

- A.C.E.™ Sequencing Buffer 10X (Amresco)
 - \$155/L = \$0.0155/mL 1X buffer (costs 20 times less!)
 - http://www.amresco-inc.com

What ABI protocols suggest

3700 POP-6 Polymer (Applied Biosystems) \$530 / 200 mL = \$2.65/mL (costs 20 times less!)

- 10X Genetic Analyzer Buffer with EDTA
 - \$78/25 mL = \$0.312/mL 1X buffer (ABI)
- 3100 POP-4 Polymer
 - \$365 / 7 mL = \$52/mL

2004 prices

Protocols Used for STR Typing

- · Most forensic DNA laboratories follow PCR amplification and CE instrument protocols provided by the manufacturer
- Comments
 - Lower volume reactions may work fine and reduce costs
 - No heat denaturation/snap cooling is required prior to loading samples into ABI 310 or ABI 3100
 - Capillaries do not have to be thrown away after 100 runs
 - POP-4 polymer lasts much longer than 5 days on an ABI 310
 - Validation does not have to be an overwhelming task

Reduced Volume PCR Amplifications

Advantages

- · Lower cost since kit contents are stretched
- · Improved sensitivity perceived due to use of concentrated PCR products (since 1 uL out of a 5 uL reaction is 20% while 1 uL out of a 50 uL reaction is 2%)

Disadvantages

- · Less volume of input DNA
 - Tighter control (improved precision) required in DNA quantitation
 - If low amount of DNA, then potential for allelic dropout (LCN conditions)
 - If PCR inhibitor is present, then less opportunity for dilution of inhibitor
- · Evaporation impacts PCR amplification performance

Publications:
Gaines et al. J Forensic Sci 2002; 47(6):1224-1237. Reduced volume PCR amplification reactions using the AmpFISTR Profiler Pus lat.
Local et al. J Forensic Sci 2003; 48(5):1001-1013. STR DNA typing; increased sensitivity and efficient sample consumption Local et al. J Forensic Sci 2003; 48(5):1001-1013. STR DNA typing; increased sensitivity and efficient sample consumption regional columns. The propriet of the Company of th

Identifiler 5 µL PCR Protocol


Identifiler PCR amplification was carried out on a GeneAmp® 9700 using 1 ng of DNA according to kit protocols with the exception of reduced volume reactions (5 μL instead of 25 μL) and reduced cycles (26 instead of 28).

Amplification products were diluted 1:15 in Hi-Di™ formamide and GS500-LIZ internal size standard (0.3 uL) and analyzed on the 16-capillary ABI Prism® 3100 Genetic Analyzer without prior denaturation

 $\mathsf{POP^{\scriptscriptstyle TM}\text{--}6}$ (3700 POP6) rather than $\mathsf{POP^{\scriptscriptstyle TM}\text{--}4}$ was utilized for higher

Allele calls were made in Genotyper® 3.7 by comparison with kit allelic ladders using the Kazaam macro (20% filter).

Butler JM, Schoske R, Vallone PM, Redman JW, Kline MC. Allele frequencies for 15 autosomal STR loci on U.S. Caucasian, African American, and Hispanic populations. *J Forensic Sci* 2003; 48(4):908-911.



Maintenance of ABI 310/3100/3130


- Syringe leaks cause capillary to not fill properly
- Capillary storage & wash it dries, it dies!
- Pump block cleaning helps insure good fill
- · Change the running buffer regularly

YOU MUST BE CLEAN AROUND A CE!

Overall Thoughts on the ABI 310/3100/3130

- Settling on a common instrument platform has been good for the forensic DNA community in terms of data consistency (this is also true with the use of common STR kits)
- I am concerned that the community is very dependent primarily on one company...
- I really like using the instrument and can usually get nice data from it
- · Like any instrument, it has its quirks...

Troubleshooting



CE Troubleshooting


Bruce McCord, AAFS 2006 Workshop (Seattle, WA February 20, 2006


Outline for This Section


- Chemistry/molecular biology problems stutter, -A, degradation, inhibition, low copy #
- 2. Sample and buffer problems formamide, urea, water, salt concentration, free dye ("dye blobs")
- 3. External factors power supply, room temperature, cleanliness, voltage leaks
- Instrument problems optical system, capillary clogging, air bubbles, syringe leaks
- 5. Troubleshooting benchmarks/QC monitoring


3. External Factors


- · Room temperature
 - Variations in room temperature can cause mobility shifts with band shifts and loss of calibration
 - Temperature is also important due to effects of high humidity on electrical conductance
- Cleanliness
 - Urea left in sample block can crystallize and catalyze further crystal formation causing spikes, clogs and other problems.
 - Best bet is to keep polymer in system and not remove or change block until polymer is used up.


































NYC OCME Forensic Biology Continuing Education Seminar




Cleanliness


- Urea sublimates and breaks down to ionic components these find a path to ground
- Similarly wet buffer under a vial creates paths to ground
- Capillary windows must be clear or matrix effects will occur
- · Laser will often assist in this process
- Vial caps will transfer low levels of DNA to capillary



4. Instrumental Factors

- · Optical System
 - Sensitivity changes with age, capillary diameter, capillary cleanliness, instrument calibration
- Fluidic System
 - Effects of bubbles, dust, urea crystals, leaks in syringe and capillary ferrule
- Matrix Calculations
 - Changes in buffer, optics, sample dye can alter the software calibrations
- Capillary Problems
 - Chemisorbed materials on capillary surface can produce osmotic flow, DNA band broadening and inconsistent resolution (meltdowns)





Beware of Urea Crystals



Pump block should be well cleaned to avoid


problems with urea crystal formation

Urea crystals have formed due to a small leak where the capillary comes into the pump block

Urea sublimates and can evaporate to appear elsewhere

Use a small balloon to better grip the ferrule and keep it tight


Storage when ABI 310 is not in use



- Remember that the water in the open tube will evaporate over time.
- Keep inlet of capillary in water...if it dries out then urea crystals from the polymer will clog the opening
- The waste vial (normally in position 3) can be moved into position
- A special device can be purchased from Suppelco to rinse the capillary off-line
- Store in distilled water
- Note that the laser is on when the instrument is on

Buffer Issues

- · The buffer and polymer affect the background fluorescence- affecting the matrix
- Urea crystals and dust may produce spikes
- High salt concentrations may produce reannealing of
- · High salt concentrations affect current
- Low polymer concentrations affect peak resolution



Meltdowns can be permanent or transitory as we have seen these may result from sample contamination effects 126 150 175 200 225 250 275 300 325 350 375 400 425 450 475 Does the capillary need to be replaced? MM AA MIRA ~ No! The next injection looks fine... #Q 50 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 1500

Meltdowns may be the result of

- · Bad formamide
- Excess salt in sample/renaturation
- · Water in the polymer buffer
- Syringe leak or bottom out
- · Poisoned capillary
- Conductive polymer buffer due to urea degradation
- Crack/shift in capillary window
- · Detergents and metal ions

NYC OCME Forensic Biology Continuing Education Seminar

5. Troubleshooting benchmarks


- · Monitor run current
- Observe syringe position and movement during a batch
- Examine ILS (ROX) peak height with no sample
- Observe "250 bp" peak in GS500 size standard
- Monitor resolution of TH01 9.3/10 in allelic ladder and size standard peak shapes
- · Keep an eye on the baseline signal/noise
- Measure formamide conductivity
- Reagent blank are any dye blobs present?
- See if positive control DNA is producing typical peak heights (along with the correct genotype)


Measurement of Current


- V/I = R where R is a function of capillary diameter, [buffer], and buffer viscosity
- In a CE system the voltage is fixed, thus changes in resistance in the capillary will be reflected in the current observed
- Air bubbles, syringe leaks, alternate paths to ground, changes in temperature, changes in zeta potential, and contamination, will be reflected in the current
- A typical current for a CE system with POP4 buffer is 8-12 μA (microamps)

Syringe Travel

- The ABI 310 instrument also keeps track of the position of the syringe (in the log file)
- Depending on the resistance to flow, the syringe will travel different lengths
- Syringe leaks may be reflected in a longer distance traveled prior to each injection
- These leaks occur around the barrel of the syringe and at the connection to the capillary block







Conclusion:

Troubleshooting is more than following the protocols

It means keeping watch on all aspects of the operation

- 1. Monitoring conductivity of sample and formamide
- 2. Keeping track of current and syringe position in log.
- 3. Watching the laser current
- 4. Watching and listening for voltage spikes
- 5. Monitoring room temperature and humidity

Multiplex_QA Article Published Devictory 2006, 12, 2735-2746 Problem May 10, 104 Substantial Science Published and Technology, 10, 104 Substantial Science Published and Technology, 10, 104 Substantial Science Published and Technology, 10, 104 Buckents May 10, 104 Buckents May 10, 104 Buckents May 11, 2006 Buckents May 11, 2006 Buckents May 11, 2006 Accepted May 11, 2006 Buckents May 11, 2006 Accepted Ma

